

SAFETY DATA SHEET

BARTOLINE - Brush Cleaner

According to Regulation (EC) No 1907/2006 Annex II as amended by Regulation (EU) 2015/830.

SECTION 1: Identification of the substance/mixture and of the company/undertaking			
1.1. Product identifier			
Product name	BARTOLINE - Brush Cleaner		
REACH registration notes	No REACH registration number required as this product is a mixture.		
1.2. Relevant identified uses of the substance or mixture and uses advised against			
Identified uses	Paint brush cleaner		
Uses advised against	Not to be used for cleaning skin as this may lead to skin disorders.		
1.3. Details of the supplier of t	he safety data sheet		
Supplier	Bartoline Limited Barmston Close Beverley East Yorkshire HU17 0LW 01482 678710 info@bartoline.co.uk		
Contact person	Product Compliance Manager		
1.4. Emergency telephone number			
Emergency telephone	01482 678710 (8.30am - 4.45pm Monday to Friday) or NHS 111 (General Public) (24 Hour service)		
National emergency telephone number	National Poisons Information Service (24hours) 0844 892 0111		
SECTION 2: Hazards identific	ation		
2.1. Classification of the subst	ance or mixture		
Classification (EC 1272/2008)			
Physical hazards	Flam. Liq. 3 - H226		
Health hazards	STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304 STOT SE 3 - H336		
Environmental hazards	Aquatic Chronic 2 - H411		
Human health	Prolonged skin contact may cause redness and irritation. Ingestion of even small quantities may be fatal. Vapours and spray/mists in high concentrations are narcotic. Prolonged contact causes serious eye and tissue damage.		
Environmental	The product contains a substance which is toxic to aquatic organisms and which may cause		

long-term adverse effects in the aquatic environment.

Physicochemical

Vapours may form explosive mixtures with air. Vapours may be ignited by a spark, a hot surface or an ember. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Containers can burst violently or explode when heated, due to excessive pressure build-up.

2.2. Label elements

Pictogram

	<
--	---



Signal word	Danger
Hazard statements	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	 P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P280 Wear Nitrile/PVC protective gloves and chemical resistant safety glasses with side shields. IF SWALLOWED: Immediately call a doctor/NHS 111. P331 Do NOT induce vomiting. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor/NHS 111 if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container to hazardous waste collection point.
Supplemental label information	Contains: GREATER THAN 30% ALIPHATIC HYDROCARBONS. 15% OR OVER BUT LESS THAN 30% AROMATIC HYDROCARBONS. LESS THAN 5% ANIONIC SURFACTANT EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
Detergent labelling	Contains: GREATER THAN 30% ALIPHATIC HYDROCARBONS. 15% OR OVER BUT LESS THAN 30% AROMATIC HYDROCARBONS. LESS THAN 5% ANIONIC SURFACTANT.
2.3. Other hazards	

SECTION 3: Composition/inf	ormation on ingredients	
3.2. Mixtures		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, 60-100% aromatics (2-25%)		
CAS number: —	EC number: 919-446-0	REACH registration number: 01- 2119458049-33-XXXX
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
Isopropylamine dodecylbenzenesulfonate 1-5%		
CAS number: 26264-05-1	EC number: 247-556-2	
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319		
The Full Text for all R-Phrase	es and Hazard Statements are Displayed in Sec	ction 16.
SECTION 4: First aid measure	res	
4.1. Description of first aid me	easures	
General information	Remove affected person from source of contamination. IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR THE NHS 111 SERVICE.	
Inhalation	Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.	
Ingestion	DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately! Provide rest, warmth and fresh air.	
Skin contact	Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.	
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms are severe or persist after washing.	
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves.	

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.	
Inhalation	Vapours inhaled in strong concentration have a narcotic effect on the central nervous system. Irritation of the respiratory tract due to excessive fume, causes headache, drowsiness or other effects to the central nervous system, loss of consciousness.	
Ingestion	If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious pulmonary lesions (medical survey during 48 hours). Nausea, Vomiting, Abdominal pain.	
Skin contact	Prolonged or repeated contact may cause irritation and dry skin.	
Eye contact	Burning feeling and temporary redness.	
4.3. Indication of any immediate medical attention and special treatment needed		
Notes for the doctor	Treat symptomatically.	
Specific treatments	The most severe risk is through ingestion, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious inhalation pulmonary lesions (medical survey during 48 hours).	
SECTION 5: Firefighting meas	ures	
5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
5.2. Special hazards arising from the substance or mixture		
Specific hazards	Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.	
Hazardous combustion products	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentrations.	
5.3. Advice for firefighters		
Protective actions during	Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the	

firefightingfire is out. Keep run-off water out of sewers and water sources. Dike for water control.
Containers close to fire should be removed or cooled with water.Special protective equipmentIn case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant

for firefighters protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. No
	smoking, sparks, flames or other sources of ignition near spillage. Do not touch or walk into
	spilled material. Do not enter storage areas or confined spaces unless adequately ventilated.
	Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,
	clothing or apron, as appropriate. Take precautionary measures against static discharges.
	Take care as floors and other surfaces may become slippery.

For non-emergency personnel	Land Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in the immediate area). Stop leak if you can do so without risk. Do not touch or walk through spilled material. Prevent entry into waterways, sewers, basements or confined areas. A vapour-suppressing foam may be used to reduce vapour. Dam or absorb spillage with non-combustible material such as earth, sand or booms, pads or absorbent granules. Use clean non-sparking tools to collect absorbed material. Water Spill: Stop leak if you can do so without risk. Eliminate sources of ignition. Warn or evacuate occupants in surrounding and downwind areas if required, due to the toxicity or flammability of the material. If the flashpoint exceeds the ambient air temperature by 10 degrees C or more, use containment booms and remove from the surface by skimming or with suitable absorbents. If the flashpoint does not exceed the ambient air temperature by at least 10 degrees C, use booms as a barrier to protect shorelines and allow material to evaporate. Seek the advice of a specialist before using dispersants.
For emergency responders	Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for

For emergency responders Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for additional information on health hazards. For waste disposal, see section 13.

6.2. Environmental precautions

Environmental precautionsThe product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. The product is insoluble in water and will spread on the water surface. Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning upStop leak if safe to do so. Eliminate all sources of ignition. No smoking, sparks, flames or
other sources of ignition near spillage. To prevent release, place container with damaged side
up. Cover large spillages with alcohol-resistant foam. Absorb spillage with non-combustible,
absorbent material. Collect spillage for reclamation or disposal in sealed containers via a
licensed waste contractor.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling			
Usage precautions	Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Use explosion proof electric equipment. Storage tanks and other containers must be grounded. Wear full protective clothing for prolonged exposure and/or high concentrations. Contaminated clothing and shoes must be discarded. Contaminated rags and cloths must be put in fireproof containers for disposal. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Avoid spilling and release to the environment such as drains and watercourses.		
Advice on general occupational hygiene	Persons with impaired lung function should not handle this product Do not eat, drink or smoke when using this product. Provide shower facilities near the workplace. Wash promptly with soap and water if skin becomes contaminated. Take off immediately all contaminated clothing and wash it before reuse. Promptly remove any clothing that becomes wet or contaminated. Remove contaminated clothing and protective equipment before entering eating areas. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.		

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep container tightly sealed when not in use. Keep locked up and out of the reach of children. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with oxidising agents. Keep away from food, drink and animal feeding stuffs. Use containers made of the following materials: Carbon steel. Glass. Mild steel. Stainless steel. High-density polyethylene (HDPE) Polyethylene terephthalate (PET)		
Storage class	Flammable liquid storage.		
7.3. Specific end use(s)			
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.		
Usage description	In General: Keep containers closed when not in use. Keep containers upright. Use only in well ventilated areas, ideally outdoors. Open containers slowly in order to release any pressure build up that may occur. Keep out of reach of children. Apply "common sense" measures when using this product. When using transfer required amount to a suitable container such as glass, metal or HDPE. Avoid all contact with skin and eyes.		

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Long-term exposure limit (8-hour TWA): 350 mg/m3 vapour

Isopropylamine dodecylbenzenesulfonate

Long-term exposure limit (8-hour TWA): NO STD NO STD

Ingredient comments

The Workplace Exposure Limited quoted is an advisory level from the CEFIC-HSPA The figures quoted below are taken from the registration document and/or the substance manufacturers data sheet.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

DNEL

Industry/Professional - Dermal; Long term systemic effects: 44 mg/kg/day Industry/Professional - Inhalation; Long term systemic effects: 330 mg/m3/8h General population - Dermal; Long term systemic effects: 26 mg/kg/day General population - Inhalation; Long term systemic effects: mg/m3/24h General population - Oral; Long term systemic effects: mg/kg/day

8.2. Exposure controls



Appropriate engineering controls	This product is not to be used under conditions of poor ventilation. This product must not be handled in a confined space without adequate ventilation. Mechanical ventilation or local exhaust ventilation may be required. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and lighting equipment. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures.
Personal protection	Protective engineering solutions should be implemented and in use before Personal Protective Equipment (PPE) is considered.
Eye/face protection	Wear EN 166 approved chemical safety goggles where eye exposure is reasonably probable.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl chloride (PVC). Viton rubber (fluoro rubber). Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear an apron and protective sleevelets made of the following material: Nitrile rubber. Polyvinyl chloride (PVC). Viton rubber (fluoro rubber). Wear anti-static protective clothing if there is a risk of ignition from static electricity.
Hygiene measures	Persons with impaired lung function should not handle this product Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Wash hands thoroughly after handling. Wash promptly if skin becomes contaminated. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Promptly remove any clothing that becomes wet or contaminated. Remove contaminated clothing and protective equipment before entering eating areas. Change work clothing daily before leaving workplace. Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin. Do not eat, drink or smoke when using this product.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate BS EN 405:2001+A1:2009 certified respirators. In the case of vapour formation use a respirator with filter model :. Type A. In case of vapours and aerosol formation:. Respirator with combination filter for vapour/particulate, Type A/P2. Warning ! filters have a limited use duration.
Thermal hazards	Not Applicable
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
SECTION 9: Physical and CI	

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Blue.
Odour	aromatic hydrocarbons
Odour threshold	Not available.
рН	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	158 – 191 degrees C 316 – 376 degrees F
Flash point	~ 40°C ISO 13736 ~ 104°F ISO 13736
Evaporation rate	~ 57 EtEt=1 DIN 53170
Evaporation factor	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 7 % Lower flammable/explosive limit: 0.7 %
Other flammability	Not applicable.
Vapour pressure	1.9 hPa @ 20°C
Vapour density	Not available.
Relative density	0.763 - 0.803
Bulk density	Not applicable.
Solubility(ies)	Substance is a UVCB. Standard tests for this endpoint are not appropriate.
Partition coefficient	Not available.
Auto-ignition temperature	>230°C/>446°F
Decomposition Temperature	Not available.
Viscosity	30 - 35 SECONDS (B2 FLOW CUP).
Explosive properties	Not considered explosive based on chemical structure and oxygen balance considerations.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.
9.2. Other information	
Volatility	Volatile.
Volatile organic compound	This product contains a maximum VOC content of 769 g/l.
SECTION 10: Stability and rea	Ictivity
10.1. Reactivity	
Reactivity	The reactivity data for this product will be typical of those for the following class of materials: Hydrocarbons. There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability		Stable under the prescribed storage conditions. See Section 10.3 (Possibility of hazardous reactions) for further information.		
10.3. Possibi	ility of hazardous r	eactions		
Possibility of reactions	hazardous	Under normal conditions of storage and use, no hazardous reactions will occur.		
10.4. Conditi	ons to avoid			
Conditions to	tions to avoid Containers can burst violently or explode when heated, due to excessive pressure build-up. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to he or sources of ignition. Avoid the accumulation of vapours in low or confined areas.			
10.5. Incomp	oatible materials			
Materials to a	avoid	Avoid cor	ntact with the following materials: Strong acids. Oxidising agents.	
10.6. Hazard	lous decompositior	n products		
•		-	te combustion and thermolysis may produce gases of varying toxicity such as carbon e, carbon dioxide, various hydrocarbons, aldehydes and soot.	
SECTION 11	I: Toxicological info	ormation		
11.1. Informa	ation on toxicologic	al effects		
Toxicological effects The Tox			city of the main hazardous constituent has been assessed through the REACH See information on individual substances below.	
Germ cell mu	utagenicity			
Genotoxicity	- in vitro	Based on available data the classification criteria are not met.		
Genotoxicity - in vivo Ba		Based on available data the classification criteria are not met.		
Toxicological information on ingredients		gredients.		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	Toxicological effect	cts	The toxicity of this substance has been assessed during REACH registration.	
	Acute toxicity - ora	al		
	Acute toxicity oral mg/kg)	(LD₅o	15,000.0	
	Species		Rat	
	ATE oral (mg/kg)		15,000.0	
	Acute toxicity - de	rmal		
Acute toxicity dermal (LD₅∞ mg/kg)		nal (LD₅₀	3,400.0	
	Species		Rat	
	ATE dermal (mg/k	(g)	3,400.0	
	Skin corrosion/irrit	tation		
	Animal data		Conclusive data but not sufficient for classification. Not irritating.	
	Serious eye dama	age/irritatio	n	

Respiratory sensitisation
Respiratory sensitisation Based on available data the classification criteria are not met.
Skin sensitisation
Skin sensitisation Based on available data the classification criteria are not met.
Germ cell mutagenicity
Genotoxicity - in vitro Based on available data the classification criteria are not met.
Carcinogenicity
Carcinogenicity Based on available data the classification criteria are not met.
Reproductive toxicity
Reproductive toxicity - Based on available data the classification criteria are not met. fertility Based on available data the classification criteria are not met.
Reproductive toxicity -This substance has no evidence of toxicity to reproduction.development
Specific target organ toxicity - single exposure
STOT - single exposure Vapours may cause drowsiness and dizziness.
Target organs Central nervous system
Specific target organ toxicity - repeated exposure
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.
Target organs Central nervous system
Aspiration hazard
Aspiration hazardMay be fatal if swallowed and enters airways. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Inhalation Vapours inhaled in strong concentrations have a narcotic effect on the central nervous system. Irritation of the respiratory tract due to excessive fume. Causes headache, drowsiness or other effects to the central nervous system, loss of consciousness.
Ingestion Symptoms: Nausea, vomiting, abdominal pain. Harmful: If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious inhalation pulmonary lesions (medical survey during 48 hours).
Skin contactProlonged or repeated contact may dry skin and cause irritation. Frequent or prolonged skin contact destroys the lipacid cutaneous layer and may cause dermatitis.
Eye contact This mixture does not meet the EU criteria for classification. Any eye contact may cause a burning feeling and temporary redness.
Route of exposure Inhalation Ingestion Oral Skin and/or eye contact
Target organs Central nervous system Eyes Skin Respiratory system, lungs

SECTION

Ecological

BARTOLINE - Brush Cleaner

Medical symptoms	Symptoms following overexposure to vapour may include the following: Central nervous system depression. Confusion, agitation and/or excitation.
Medical considerations	The following pre-existing or historic medical conditions of the worker may lead to an increased risk of adverse health effects following exposure to this product: Chronic respiratory and obstructive airway diseases. History of smoking. Pre- existing eye problems. Skin disorders and allergies.
	Isopropylamine dodecylbenzenesulfonate
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	2,001.0
Species	Rat
ATE oral (mg/kg)	2,001.0
12: Ecological Information	
l information on ingredients.	
Lludroo	arbana CO C12 n alkanaa jaaalkanaa ayaliga aramatiga (2.25%)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Ecotoxicity Toxic to aquatic life with long lasting effects. 12.1. Toxicity Toxicity See information on ingredient substances below. Ecological information on ingredients. Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Acute aquatic toxicity Acute toxicity - fish LL₅₀, 96 hours: 10-30 mg/l, Oncorhynchus mykiss (Rainbow trout) Acute toxicity - aquatic EC50, 48 hours: 10-22 mg/l, Daphnia magna invertebrates Acute toxicity - aquatic EC50, 72 hours: 4.1 mg/l, Pseudokirchneriella subcapitata plants Chronic aquatic toxicity Chronic toxicity - fish early NOEC, 28 days: 0.13 mg/l, Oncorhynchus mykiss (Rainbow trout) life stage Chronic toxicity - aquatic NOEC, 21 days: 0.28 mg/l, Daphnia magna invertebrates

12.2. Persistence and degradability

Persistence and degradability The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request, or at the request of a detergent manufacturer.

Ecological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Persistence and degradability	Readily biodegradable (75 % after 28 days).
12.3. Bioaccumulative potenti	al
Partition coefficient	Not available.
Ecological information on ingr	edients.
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
Bioaccumulative	potential Measured experimental data on hydrocarbon UVCB substances are not meaningful, since each of the constituents is likely to behave differently.
12.4. Mobility in soil	
Mobility	Substance is a UVCB. Standard tests for this endpoint are not appropriate.
Ecological information on ingr	edients.
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
Mobility	Substance is a UVCB. Standard tests for this endpoint are not appropriate.
12.5. Results of PBT and vPv	B assessment
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
Ecological information on ingr	redients.
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
Results of PBT and vPvB This substance is considered not to be PBT and vPvB. assessment	
12.6. Other adverse effects	
SECTION 13: Disposal consid	lerations
13.1. Waste treatment method	ds
General information	The generation of waste should be minimised or avoided wherever possible. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. External recovery, treatment, recycling and disposal of waste should comply with all applicable local and/or national regulations. Waste material and any included combustible absorbent and containers should be suitable for incineration at an approved facility. This material and its container must be disposed of as hazardous waste. Waste packaging should be collected for reuse or recycling. The packaging must be empty (drop-free when inverted). When handling waste, the safety precautions applying to handling of the product should be considered.
Disposal methods	Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Waste material and any included

combustible absorbent and containers should be suitable for incineration at an approved

facility. This material and its container must be disposed of as hazardous waste.

Waste class	When this product, in its liquid state, as supplied becomes waste it should be disposed of as hazardous waste using the waste code 08 01 11 waste paint and varnish containing organic solvents or other dangerous substances. Empty used containers should be disposed of as waste code 15 01 10 packaging containing residues of or contaminated by dangerous substances. When used the removed sludge should be disposed of using waste code 08 01 13 sludges from paint and varnish remover containing organic solvents or other dangerous substances. Any absorbents used for clearing up spills should be disposed of using waste code 15 02 02 absorbents contaminated by dangerous substances.
SECTION 14: Transpor	rt information

General	For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section. Limited quantity size 5 litres (LQ 7) Excepted Quantity size 30ml (E1)	
14.1. UN number		
UN No. (ADR/RID)	1263	
UN No. (IMDG)	1263	
UN No. (ICAO)	1263	
UN No. (ADN)	1263	
14.2. UN proper shipping nam	14.2. UN proper shipping name	
Proper shipping name (ADR/RID)	PAINT RELATED MATERIAL	
Proper shipping name (IMDG	PAINT RELATED MATERIAL	
Proper shipping name (ICAO)	PAINT RELATED MATERIAL	
Proper shipping name (ADN)	PAINT RELATED MATERIAL	
14.3. Transport hazard class(es)		
ADR/RID class	3	
ADR/RID classification code	F1	
ADR/RID label	3	
IMDG class	3	
ICAO class/division	3	
ADN class	3	
Transport labels		



14.4. Packing group	
ADR/RID packing group	111
IMDG packing group	
ADN packing group	
ICAO packing group	111

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user	
EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y

Hazard Identification Number 30 (ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended). Dangerous Substances and Explosive Atmospheres Regulations 2002. EH40/2005 Workplace exposure limits. Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient assessment of all the risk should be undertaken before using this product. The guidelines given in the HSE publication COSHH ESSENTIALS - Easy Steps To Control Chemicals gives sound advice for deciding safe working control measures.
EU legislation	Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments. Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended). Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	CHIP for everyone HSG228. Introduction to Local Exhaust Ventilation HS(G)37. The spraying of flammable liquids HSG178. Workplace Exposure Limits EH40.

Health and environmental listings	Regulation (EC) 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals (as amended).
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	The European Inventory of Existing Commercial Substances (EINECS) descriptions and numbers have been used historically to identify chemical substances. EINECS descriptions exist for a number of hydrocarbon substances derived from petroleum refining and chemical conversion. In the past this substances was identified by CAS 64742-82-1 but this description was overly broad as solvents have narrower hydrocarbon ranges. different classifications and different processing. A more focused and narrow definition was therefore required. REACH requires a clear and logical substance description and substance identification is a key component in registration. In order to facilitate appropriate registration of hydrocarbon solvents the Hydrocarbon Solvents Producers Association (HSPA) has conducted an in-depth assessment of hydrocarbon solvents in order to better characterize its substances and adopt a consistent substance identification system. This means that although the product has not changed (just how is described) there may be some difference as to what is displayed on the product labels as they were compiled using the old system.
Classification procedures according to Regulation (EC) 1272/2008	: Calculation method.
Training advice	The information on directions for use can be found on the product label. It is important to ensure that anyone using this product in the workplace has been adequately trained and in particular: The use of personal protective equipment, methods of cleaning up and disposal of waste. The basic first aid arrangements.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision. DUE TO CHANGE OF CLASSIFICATION DATABASE THE REVISION NUMBERING HAS BEEN RESET. You should therefore look at the revision date rather than the revision number to ensure you have the most up to date version.
Issued by	Product Compliance Assistant
Revision date	26/11/2018
Revision	3
Supersedes date	22/03/2017
SDS number	4656
SDS status	Approved.

Risk phrases in full	 R10 Flammable. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R66 Repeated exposure may cause skin dryness or cracking. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	 H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.

The information contained in this data sheet is provided in accordance with the requirements of the Regulation (EC) No 1907/2006 Annex II as amended by Regulation (EU) 2015/830 and Regulation (EC) No 1272/2008 (CLP). The product should not be used for purposes other than those shown in Section 1.2. As the specific conditions of use are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet is based on the present knowledge and the current EU and UK Legislation. It provides guidance on health, safety and environmental aspects of the product and should not be taken as a product specification.